


Electrical

Advance constant current electronic drivers multi voltage meets UL 1310 / UL48 Class 2 with a built-in over-temperature protection. Input voltage from 100-277. 347 and 480 volt is available (VAC 50-60Hz) Certified and tested to the North American UL 1598C LED Conversion Standard.

Lamping

Phillips Luxeon light emitting diodes (LED) mounted on heavy weight metal modular boards utilizing wire to board push-in connectors. Optical Quality Polymethyl Methacrylate (PMMA) Optics provide wide coverage uniform lighting distributions available in I.E.S. distributions : type 2, 3, 4, 5



Auraform

Light Emitting Diode Retrofit Kit. Luminaire

ENVIRONMENTAL FEATURES




- *Contains no mercury or lead
- *Does not produce UV rays
- *Does not attract insects
- *Directional light means no light pollution

FEATURED HIGHLIGHTS

- *Unlimited application possibilities due to retrofitting
- *Saves up to 79% of energy consumption
- *70,000 hour life span 5yr. Manufacturers warranty
- *Return on Investment between 12 to 24 months.






Auraform Two, Auraform Three Conversion Kits.

	Lamp Wattage Distribution	LED Color	Voltage
RK-AU2			
48 watt LED Type 2	(48LED 2)	3500K  4000K  5000K 	MT (120-277)
48 watt LED Type 3	(48LED 3)		347
48 watt LED Type 4	(48LED 4)		480
48 watt LED Type 5	(48LED 5)		
60 watt LED Type 2	(60LED 2)		6,800 Lms
60 watt LED Type 3	(60LED 3)		6,800 Lms
60 watt LED Type 4	(60LED 4)		6,800 Lms
60 watt LED Type 5	(60LED 5)		6,800 Lms
96 watt LED Type 2	(96LED 2)		10,700 Lms
96 watt LED Type 3	(96LED 3)		10,700 Lms
96 watt LED Type 4	(96LED 4)		10,700 Lms
96 watt LED Type 5	(96LED 5)		10,700 Lms



Rotatable Optics

Auraform One, Conversion Kits.

	Lamp Wattage Distribution	LED Color	Voltage
RK-AU1			
120 watt LED Type 2	(120LED 2)	3500K  4000K  5000K 	MT (120-277)
120 watt LED Type 3	(120LED 3)		347
120 watt LED Type 4	(120LED 4)		480
120 watt LED Type 5	(120LED 5)		
150 watt LED Type 2	(120LED 2)		17,000 Lms
150 watt LED Type 3	(120LED 3)		17,000 Lms
150 watt LED Type 4	(120LED 4)		17,000 Lms
150 watt LED Type 5	(120LED 5)		17,000 Lms
180 watt LED Type 2	(180LED 2)		20,400 Lms
180 watt LED Type 3	(180LED 3)		20,400 Lms
180 watt LED Type 4	(180LED 4)		20,400 Lms
180 watt LED Type 5	(180LED 5)		20,400 Lms



Pappi Lighting

5939 Wallace, St.
Mississauga, ON
Canada L4Z 1Z8
tel: (905) 625-1139
tel: (888) 453-1139
fax: (866) 720-3015
www.pappilighting.com